

TeleControl Serie 24 , Doble Joystick Alcance 300Mts



Características Esenciales

- 1 Años de Garantía, Partes y Servicios Disponibles en América

Especificaciones Técnicas

Control Speed	5 Speed	Código de Seguridad	32 bits (4.3 billion)
Channels	2 x 4 Direction Joystick	Potencia del Transmisor	≤10dBm
Transmitter Emergency Stop	Yes	Rango de Frecuencia	VHF: 310~331 MHz; UHF: 425 ~ 446 MHz
Código FCC	OFNF21	Rango de temperatura de Trabajo	-40 ~ 185 °F / -40 ~ 85°C
Fuente de Alimentación del Transmisor	2 AA batteries	Normas	FCC and OSHA standard 1910.179
Sensibilidad del Receptor	dBm -112	Garantía	1 Year
Distancia de Control	300 ft / 100 mt		

► F24-60 TRANSMITTER

Intelligent, powerful, safe, reliable, outstanding



MODEL: F24-60-TX
ITEM CODE: 924-600-001
Dimension: 210 x 152 x 128 mm
Weight: 980g (without batteries)



F24-60

Product features

- 6 buttons, 4 three-position or two-position rotating switch, stop, start, spare button.
- 2 five-step joysticks with 10 million times of mechanical life and pure proportion.
- Up to 40 control contacts
- With battery voltage warning device, the power supply is cut off during low power
- Safety switch key is to prevent from unauthorized user
- Program the button function by computer interface
- Start key can be programmed to start, toggle switch, normal or other functions
- The spare buttons can be programmed to start, toggle, interlock or normal, etc
- Installed with proportional module for analog signal output (optional)

Standard Configuration

- One transmitter (with waist belt)
- One receiver
- Receiver with 2.5 meter cable
- Battery: two pairs
- One receive antenna
- One battery box
- Operation and maintenance manual

Transmitter Parameters: F24-TX

Material	Glass-Fiber PA
Enclosure protection class	IP65
Frequency range	VHF: 310~331MHz; UHF: 425~446MHz
Transmitter power	≤10dBm
Transmitter power supply	2 AA batteries
Safety code	32 bits (4.3 billion)
Temperature range	-40°C~+85°C
Control distance	Approx 300m



► F24-60 RECEIVER

TELEcontrol

MODEL: F24-60-RXC
ITEM CODE: 924-610-011
Dimension: 320x253x107mm
Weight: 2020g



As double joystick remote control, F24-60 is one of the most advanced crane controllers on the market and it is developed in ISO9001 certified factory with more than 21 years history.

F24-60 is designed with strong safety features. It has more than 4.3 billion unique safety code, automatic frequency tracking and locking and failure self-diagnosis, etc. Stop button is automatic. When components such as switches, joysticks, or relays are in fault, the system stops working till it is fixed.

F24-60 has extraordinary communication design—simultaneous encoding and decoding transmission, interference elimination, error detection and correction, and frequency resettable manually.

F24-60 has large amounts of programmable functions and is extensible using Windows compatible software with free update. Functions are all programmable.

Receiver Parameters: F24-RXC

Material	Glass-Fiber PA
Enclosure protection class	IP65
Frequency range	VHF: 310~331MHz; UHF: 425~446MHz
Receiver sensitivity	-110dBm
Receiver power supply	18~65V AC/DC, 65~440V AC/DC (optional)
Output contactor capacity	8A sealed relay output (with AC 250V/10A relays, 10A fuse)
Control distance	Approx 300m
Safety code	32 bits (4.3 billion)
Temperature range	-40°C~+85°C



The green technology innovation
The green design of power supply is to enhance not only the products adaptability on the environment, but also the



Peso & Dimensiones

Peso Total

10 lbs / 5 Kg

Referential Images / Imágenes Referenciales

Specifications may change without notice / las especificaciones pueden cambiar sin previo aviso